



Features

- **Wall-mount Cast Aluminum Enclosure**
- **Simple Cabling with 2 wires, star feed**
- **Modern digital SMD technology**
- **600 Ohm External Audio**
- **Private full duplex handset communication**
- **Headset, gooseneck microphone and handset options**
- **Single touch speed dialing**
- **UL-Listed for Division 2 Hazardous Areas**

The GAI-Tronics DHS/DHF/DSA Series Digital Intercom Stations are designed for use in hazardous and non-hazardous area communications, both indoors and outdoors, and in high noise areas.

The DHS/DHF/DSA Series Digital Intercom stations are ideal for both large and small intercom systems. The systems can be upgraded to include alarms, radio interface, telephone interface, music, etc. All communication to the station is via a two-wire digital communication line.

The DI station provides instantaneous high speed connections and clear, crisp digital voice quality. Each station offers single-button all call, priority emergency paging, group paging, speed dial, conference



Benefits

- **Rugged Design, stands up to harsh industrial environments**
- **Provides safe communication in Hazardous areas**
- **Simple installation**
- **16-button keypad with configurable buttons**
- **Allows hands-free communications**
- **Allows users flexibility to choose point-to-point call, group call, all-call, priority call, and conference call**

call, and relay output. Any station can call any other station(s) in a Digital Intercom System. With the headset or gooseneck microphone options, each is capable of hands-free voice communication.

The stations have direct access by using the keypad, pre-programmed keys or speed dials. This allows the user the capability of performing point to point private calls. Additionally, the system may be configured to allow group calls, conference calls and all call announcements.

A Windows based configuration tool allows the user to program the system parameters and update the system setting when required.

Technical Specifications

Wall-Mount Intercom

Power Input	AC Power: 24 V, 50/60 Hz DC Power: 24 V
Frequency Response	200–7,000 Hz, +0/-3 dB ref. @ 1 kHz
Housing	Cast aluminum painted safety orange
Physical size	9.5 H × 8.0 W × 4.0 D inches (241.3 × 203.2 × 101.6 mm)
Operating Environment	-4°F to + 140° F (-20° C to +60° C)
Weight	DHF-201: 8.0 lbs. DHF-201GN: 8.7lbs. DHF-202: 8.7 lbs. DHS-201: 9.2 lbs.
Mounting	Wall Mounted

Remote Speaker Amplifier

Power Input	AC Power: 24 V, 50/60 Hz DC Power: 24 V
Frequency Response	200–7,000 Hz, +0/-3 dB ref. @ 1 kHz
Housing	Cast aluminum painted safety orange
Physical size	9.5 H × 8.0 W × 4.0 D inches (241.3 × 203.2 × 101.6 mm)
Operating Environment	-4°F to + 140° F (-20° C to +60° C)
Weight	DSA-201: 7.0 lbs.
Mounting	Wall Mounted

Model Numbers

Hazardous Wall-Mount Handset Intercom (NRTL Div. 2) **DHS-201**

Hazardous Wall-Mount Hands-free Intercoms (NRTL Div. 2)
Single Button **DHF-201**
16 Button Keypad **DHF-202**

Wall-Mount Hands-free Intercom (NRTL Div. 2)
16 Button Keypad with Gooseneck **DHF-201GN**

Hazardous Remote Speaker Amplifier (NRTL Div. 2) **DSA-201**

Approvals

Designated models are NRTL (UL) Listed for Class I, Division 2, Groups, A,B,C, and D; Class II, Division 2, Groups F and G; Class III, Division 2 hazardous locations.

Pub. 080301 Rev. 8/2011



GAI-Tronics® USA (Corporate) Toll Free: 1 (800) 492-1212 Tel: (610) 777-1374 Fax: (610) 796-5954 www.gai-tronics.com
 GAI-Tronics® UK Tel: +44 (0)1283 500500 Fax: +44 (0)1283 500400 www.gai-tronics.co.uk
 GAI-Tronics® S.r.l - Italy Tel: +39 02 4588801 Fax: +39 02 93663110 www.gai-tronics.it
 GAI-Tronics® Malaysia Tel: +60-3-8945-4035 / 8945-7348 Fax: +60-3-8945-4675 www.gai-tronics.com
 GAI-Tronics® Austdac - Australia Tel: 011-61-28-851-5000 Fax: 011-61-29-899-2490 www.austdac.com.au

Quality Management System Certified by DNV - ISO 9001:2008

The policy of GAI-Tronics is one of continuous improvement; therefore the company reserves the right to change specifications without notice.